



Candle Grade	Features
Sterasyl	Silver Impregnated Ceramic Microfilter
Super Sterasyl	Sterasyl Microfilter Plus Granular Activated Carbon

Specification:

- Diameter Dimension: 2" (Standard), 3 1/2" (Imperial)
- Length: =10"
- Single Open End / Double Open End (OBE)
- Mount Sizes : Single Open End with a 1/4" BSP threaded mount in 3/4" (short mount)

Performance Claims

Contaminant	Supercarb	Sterasyl
Taste & Odour	✓	✗
Chlorine Reduction	> 90%	✗
Lead Reduction	✗	✗
Giardia/ Cryptosporidium	> 99.999%	> 99.999%
Particulate Removal	> 99.9% > 99.99%	> 99.9% > 99.99%
E-Coli/Vibrio Cholera/Klebsiella	> 99.99%	> 99.99%
Shigella/Salmonella Typhi	> 99.999%	> 99.999%
Turbidity	> 99.69%	> 99.69%
Capacity (USG) (Litres)	1000 3750	1500 5625
Recommended Flow Rate: (USG/Min) (L/Min)	1 3.75	1.33 5.00
Working Temp. Range (°C)	5 - 42 °C	5 - 42 °C
Working pH Range	5.5 - 9.5	5.5 - 9.5
Minimum Working Pressure	10 psi	10 psi
Maximum Working Pressure	100 psi (7 bar)	100 psi (7 bar)

Code	Candle Grade	Packing	Price
DOU-CAR	Suprecarb with carbon	25pcs/CTN	RM130.00

Code	Candle Grade	Packing	Price
DOUSTD	Sterasyl	25pcs/CTN	RM52.00



GA2 /1 MICON PP FIBER

Code	GA2-1
Packing	60pcs/CTN
Price	RM6.50



GA CTO CARBON BLOCK

Code	CTO-SILVER
Packing	25pcs/CTN
Price	RM13.00